

Tier 2

A lightweight, compact, direct-injection 4-cylinder engine

4JG1

- Environmental performance that meets Tier 2 regulations
- Powerful 46.3 kW output
- Environmentally friendly and economical with low fuel consumption
- Lightweight and compact, with outstanding quiet performance
- Highly rated around the world for reliability and durability
- ▶ Suitable for a wide range of applications








nbine Ge


* Image shown may not reflect actual engine configuration.

Engine data for general power specifications

Specifications			
Engine Model		4JG1	
Engine Characteristics		4-Cycle, Water-Cooled, Vertical In-Line	
Valvetrain Configuration		Over Head Valve	
Type of Aspiration		Naturally Aspirated	
Type of Injection		Direct	
No. of Cylinders		4	
Bore x Stroke		95.4 x 107 mm	3.75 × 4.21 in
Displacement		3.059 liters	186 cu.in
Overall Dimensions	Length	812 mm	31.96 in
	Width	569 mm	22.40 in
	Height	779 mm	30.66 in
Dry Weight		244 kg	538 lb
Rated Output		46.3 / 2600 kW/min ⁻¹	62.1 / 2600 HP/rpm
Max. Torque		195 / 1800 N·m/min ⁻¹	143 / 1800 lb·ft/rpm


^{*} The data on this data sheet are for information purposes only and are not binding values.






^{*} Appearance diagrams shown may not reflect actual engine configuration.


Performance Curve



Power Output



Fuel Consumption



^{*} Performance curves shown are representative.



^{*} Final dimensions are dependent on selected options.