

Tier 2

A 132.3 kW turbo-charged 6-cylinder engine

6BG1TC

- Environmental performance that meets Tier 2 regulations
- Powerful 132.3 kW output
- Environmentally friendly and economical with low fuel consumption
- Lightweight and compact, with outstanding quiet performance
- Highly rated around the world for reliability and durability
- ▶ Suitable for a wide range of applications





ator Gen


* Image shown may not reflect actual engine configuration.


Engine data for general power specifications

Specifications

Engine Model		6BG1TC	
Engine Characteristics		4-Cycle, Water-Cooled, Vertical In-Line	
Valvetrain Configuration		Over Head Valve	
Type of Aspiration		Turbocharged and Charge Air Cooled	
Type of Injection		Direct	
No. of Cylinders		6	
Bore x Stroke		105 x 125 mm	4.13 × 4.92 in
Displacement		6.494 liters	396 cu.in
Overall Dimensions	Length	1201 mm	47.28 in
	Width	722 mm	28.42 in
	Height	971 mm	38.22 in
Dry Weight		463 kg	1021 lb
Rated Output		132.3 / 2200 kW/min ⁻¹	177 / 2200 HP/rpm
Max. Torque		637 / 1800 N·m/min ⁻¹	469 / 1800 lb·ft/rpm


^{*} The data on this data sheet are for information purposes only and are not binding values.






^{*} Appearance diagrams shown may not reflect actual engine configuration.


Performance Curve



Power Output



Fuel Consumption



* Performance curves shown are representative.



Engines Plus Ltd

^{*} Final dimensions are dependent on selected options.