

ISUZU
DIESEL

2C
SERIES

Stage V


Dependable Power

2CA1 - 10.5 kW @ 3600 r/min (Variable Speed))

2CA1 - 8.3 kW @ 3000 r/min (Constant Speed)

THE GO-TO-ENGINE


(that goes to work)



Lightweight, compact, environmentally friendly, economical industrial diesel engine which is highly rated around the world. This engine complies with current legislation requiring no after treatment at present.

Standard

- Water cooled indirect diesel engine
- 12v Starter and Alternator
- Electric fuel pump for ease of priming
- Glow Plug starting Aid
- 500 hour oil drain & service intervals



Available Options


- Side or bottom drain oil pan
- SAE A Gear Case PTO
- Flywheel housings: SAE5 or flat plate
- Cooling packages
- Air cleaners
- Engine Control Panel and Wiring Harness
- Engine mounting
- Weather and sound-proofing enclosure

Certifications

U.S. EPA Tier 4

EU Stage V

2C



Applications



ISUZU
DIESEL

ISUZU DIESEL **2C** SERIES **The Strength to Work Harder.**

Model		2CA1
Emission Regulation	EU	Stage 5
	USA	Interim Tier 4
Type		Vertical 4-Cycle Liquid Cooled Diesel
Number of Cylinders		2
Bore	mm	70
Stroke	mm	74
Displacement	L	0.57
Combustion System		InDirect
Intake System		Naturally Aspirated
Maximum Speed	rpm	3600
Gross Rating	kW	10.5
	Bhp	14.1
Continuous Rating	kW	9.3
	Bhp	12.5
Generating Set Rating	kW	8.3
	Speed	3000r/min
Oil Pan Capacity		2.2 Litres
Starter Capacity		12v-1.1 kW
Alternator Capacity		12v-40 Amps
Dry Weight (engine only)		84 kg

