

**5** OUTBOARD  
YEARS  
warranty

FOR LEISURE USE ONLY  
Subject to terms and conditions  
see your Dealer for more  
information

**QuattroT**  
*XSR*

**QuattroT**



**f** Selva Marine



OUTBOARD  
MOTORS

## OUTBOARD MOTORS

**44** powerful  
companions  
of navigation

**QuattroT**  
**XSR**

**QuattroT**

**44** models

**2** range

Power from **2.5** Hp  
to **2x300** Hp

**5** years warranty

Selva Marine engines  
come with a five-year  
limited warranty.  
Certain conditions  
and exclusions apply  
including professional  
and commercial use.

OUTBOARD  
**5 YEARS**  
warranty

FOR LEISURE USE ONLY  
Subject to terms and conditions  
see your Dealer for more  
information

*Come closer look...*

*There are a number of boating solutions waiting for you. Whether you prefer the elegance and relaxation of a lake, speed with open sea adventures or the thrill of powering from one island to another, **Selva Marine** will accompany you providing power, control and great service.*

*The wonderful world of powerboating is now affordable and ready. Reach inlets with your friends, enjoy a beautiful sunset with your partner, or amaze everyone with landscapes that will remain in their hearts together with a lifetime passion for the sea. This is the **Selva Marine** world, a constant surprise to enjoy. Join it now.*





## **10** MODELS FROM 25HP TO 2X300HP IN 22 VERSIONS

Burning acceleration and low consumption are the main characteristics of the Selva Marine 4-stroke range for leisure, professional or commercial use. So they are specially developed for the most demanding people. The advanced electronic system controls all the engine's functions in the best way and gives breathtaking performance and fuel economy.

p. 4



## **34** MODELS FROM 2,5HP TO 2X300HP IN 105 VERSIONS

This Selva Marine range has a strong and distinctive personality that operates in total respect of nature. The use of sophisticated technologies, their compactness, elegant and innovative design make these outboard motors a range that does not go unnoticed in the pleasure boating sector.

p. 10

## Amberjack

25XSR



## Dorado E.F.I.

60XSR



## Murena E.F.I.

70XSR



# Spearfish E.F.I.

## 100XSR



# TECHNICAL CHARACTERISTICS

NEW

Model	AMBERJACK	DORADO	MURENA	SPEARFISH
Power (hp)	25 XSR EFI	60 XSR EFI	70 XSR EFI	100 XSR EFI
Power (kW)	18,4	44,1	51,5	73,6
Max. R.P.M.	5000 / 6000		5300/6300	5000/6000
Motor type	4 temps SOHC		4 temps SOHC - 16V	
Swept volume c.c.	432	996		1832
Bore x Stroke (mm)	65 x 65,1	65x75		81x88,9
N° Cylinders	2 in-line	4 in-line		
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 23			Not provided
Lubrication	Forced (oil sump)			
Ignition	C.D.I. Micro-computer	T.C.I. / Computer		
Ignition timing	Electronic			
Starting	Manual or Electric	Electric		
Alternator	Standard 12V/190 W (regulator optional) on Manual start version Standard 12V/190 W with regulator on Electric start version	Standard 12V/200W with regulator		Standard 12V/420W with regulator
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version		Remote with remote control box	
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch			
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version		Power Trim/Tilt	
Gears	Mechanical F-N-R			
Transmission Ratio	13 / 27		13/24	12/28
Available shaft versions	C. - L.	L.	L-XL	
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	56		111	119
				162

Some models may not be available in all countries or they may have different, non-standard horsepower depending on the different national legislative requirements. (For further details see the current price list.)  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

## Swordfish E.F.I.

115XSR



## Killer Whale E.F.I.

150XSR



## Sei Whale E.F.I.

200XSR



# White Whale E.F.I.

300XSR



## TECHNICAL CHARACTERISTICS

Model	SWORDFISH	KILLER WHALE	SEI WHALE	WHITE WHALE
Power (hp)	<b>115 XSR EFI</b>	<b>150 XSR EFI</b>	<b>200 XSR EFI</b>	<b>300 XSR EFI</b>
Power (kW)	84,6	110,3	147,1	220,7
Max. R.P.M.	5300/6300	5000/6000		
Motor type	4 Stroke DOHC - 16V		4 Stroke DOHC - 16V at variable timing	4 stroke DOHC - 24V with VTC direct acting
Swept volume c.c.	1832	2670	2785	4169
Bore x Stroke (mm)	81x88,9	94x96,2	96 x 96,2	96 x 96
N° Cylinders	4 on line			6 a V 60°
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Not provided			
Lubrication	Forced (oil sump)			
Ignition	T.C.I./Computer			
Ignition timing	Electronic			
Starting	Electric			
Alternator	Standard 12V /420W with rectifier		Standard 12V / 500W with rectifier	Standard 12V / 840W with rectifier
Cooling	A eau avec circulation forcée par pompe			
Exhaust	Sous-marin à travers le moyeu de l'hélice			
Steering system	Remote with remote control box		Remote control box with <b>electronic control Drive By Wire</b>	
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch	Remote control box with electronic control Drive By Wire	Remote control box with electronic control Drive By Wire	
Trim adjustment	Power Trim/Tilt			
Gears	Mechanical F-N-R		Mechanical F-N-R electronic, operating Drive by Wire	
Transmission Ratio	13/28	14/28	14/26	21/12
Available shaft versions	L-XL		XL	XL - UL
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	175	216	227	260

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

COUNTER ROTATING PAIR

**Sei Whale** E.F.I.

2x200XSR



**White Whale** E.F.I.

2x300XSR





# TECHNICAL CHARACTERISTICS

Model	COUNTER ROTATING PAIR <b>SEI WHALE</b>	COUNTER ROTATING PAIR <b>WHITE WHALE</b>
Power (hp)	<b>2 x 200 XSR EFI</b>	<b>2 x 300 XSR EFI</b>
Power (kW)	2 x 147,1	2 x 220,7
Max. R.P.M.	5000 / 6000	
Motor type	4 Stroke DOHC - 16V at variable timing	4 stroke DOHC - 24V with VTC direct acting
Swept volume c.c.	2 x 2785	2 x 4169
Bore x Stroke (mm)	2 x 96 x 96,2	2 x 96 x 96
N° Cylinders	2 x 4 on line	2 x 6 a V 60°
Induction	Electronic Injection	
Choke	Automatic	
Fuel	Petrol (for specifications see the user manual)	
Fuel tank (L)	Not provided	
Lubrication	Forced (oil sump)	
Ignition	T.C.I./Computer	
Ignition timing	Electronic	
Starting	Electric	
Alternator	Standard 2 x 12V / 500W with rectifier	Standard 2 x 12V / 840W with rectifier
Cooling	Water cooled with pump-forced circulation	
Exhaust	Underwater through propeller	
Steering system	Remote control box with <b>electronic control Drive By Wire</b>	
Type of remote control box provided (for the version with remote control box)	Twin lever with electronic binnacle Drive by Wire with safety switch	
Trim adjustment	Power Trim/Tilt	
Gears	Mechanical F-N-R electronic, operating Drive by Wire	
Transmission Ratio	14/26	21/12
Available shaft versions	XL	XL - UL
Standard propeller type	3-bladed with built-in spring drive	
Weight basic version (kg)	2 x 227	2 x 260

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## Guppy

2.5



## Sea Bass

4/5



## Sea Bass

6



# Oyster

6



## TECHNICAL CHARACTERISTICS

Model	GUPPY	SEA BASS			OYSTER
Power (hp)	2,5	4	5	6	6
Power (kW)	1.84	2.9	3.7	4.4	4.4
Max. R.P.M.	4500 / 5500	5000 / 5500			
Motor type	4 temps OHV	4 temps SOHC			
Swept volume c.c.	87	118			135
Bore x Stroke (mm)	54 x 38	56 x 48			57 x 53
N° Cylinders	1				
Induction	1 carburettor				
Choke	Manual				
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Integrated 0.9	Separate 12 or Integrated 16			Separate 12 or Integrated 18
Lubrication	Forced	Automatic oil injection into fuel			Forced with mechanical lobe-pump
Ignition	C.D.I. Digital				
Ignition timing	Electronic				
Starting	Manual				
Alternator	Not available	Optional 12V/70W with rectifier			
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment				
Trim adjustment	Manual (4 pos)	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical A-F + 360° shaft rotation	Mechanical F-N-R + 360° shaft rotation			
Transmission ratio	13 / 28	13 / 30			
Available shaft versions	C.	C. - L.			
Standard propeller type	3-bladed	3-bladed with built-in spring drive			
Weight basic version (Kg)	13.5	23			27

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## Oyster B.F.

6



## Oyster B.F. Sail

6



## Black Bass

8





## Black Bass B.F.

8



## TECHNICAL CHARACTERISTICS

Model	OYSTER BIG FOOT	OYSTER BIG FOOT SAIL	BLACK BASS	BLACK BASS BIG FOOT
Power (hp)	6	6	8	8
Power (kW)	4.4	4.4	5.9	5.9
Max. R.P.M.	5500 / 6000			
Motor type	4 Stroke SOHC			
Swept volume c.c.	135		165	
Bore x Stroke (mm)	57 x 53		63 x 53	
N° Cylinders	1			
Induction	1 carburettor			
Choke	Manual or Electrical		Manual	Manual or Electrical
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 12		Separate 12 or built-in 18	Separate 12
Lubrication	Forced with mechanical lobe-pump			
Ignition	C.D.I. Digital			
Ignition timing	Electronic			
Starting	Manual or Electric also with integrated ISB battery (not available in versions with built-in tank)			
Alternator	Optional 12V/70W with rectifier on Manual start version Standard 12V/70W with rectifier on Electric start version			
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box		Tiller bar steering with twist grip throttle control and steering friction adjustment	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch		Not applicable	Single lever with safety switch
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical F-N-R		Mechanical F-N-R + 360° shaft rotation	Mechanical F-N-R
Transmission Ratio	13 / 27		13 / 30	13 / 27
Available shaft versions	C. - L.	XL	C. - L.	
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	30.5	32	27	30.5

Certains modes peuvent ne pas être disponibles dans certains pays, ou peuvent avoir des puissances différentes, non standard, en fonction des lois nationales en vigueur (pour de plus amples informations consultez la liste des prix en vigueur).  
Les données figurant dans ce tableau doivent être considérées comme approximatives, **Selva Marine** se réservant le droit de modifier les caractéristiques techniques, les matériaux, la construction, les poids, couleurs et les graphiques, sans avertissement préalable ni obligations.

## Black Bass

*B.F. Sail*

8



## Ray

8



## Piranha

9.9



## Piranha Sail

9.9



## TECHNICAL CHARACTERISTICS

Model	BLACK BASS BIG FOOT SAIL	RAY	PIRANHA	PIRANHA SAIL
Power (Hp)	8	8	9,9	9,9
Power (kW)	5,9	5,9	7,3	7,3
Max. R.P.M.	5500 / 6000	5000 / 6000	5500 / 6000	
Motor type	4 Stroke SOHC			
Swept volume c.c.	165	212	181	
Bore x Stroke (mm)	63 x 53	56 x 43	66 x 53	
N° Cylinders	1	2 in-line	1	
Induction	1 carburettor			
Choke	Manual or Electrical	Manual	Manual or Electrical	
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 12			
Lubrication	Forced with mechanical lobe-pump	Forced (oil sump)	Forced with mechanical lobe-pump	
Ignition	C.D.I. digitale	C.D.I. Micro-computer	C.D.I. digitale	
Ignition timing	Electronic			
Starting	Manual or Electrical also with integrated ISB battery	Manual	Manual or Electrical also with integrated ISB battery	
Alternator	Optional 12V/70W with rectifier on Manual start version Standard 12V/70W with rectifier on Electric start version	Standard 12V/70W (regulator optional)	Optional 12V / 70W with regulator (A. M.) Standard 12V / 70W with regulator (A.E.)	
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box	Tiller bar steering with twist grip throttle control and steering friction adjustment	Tiller bar steering with twist grip throttle control and steering friction adjustment	
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch	Accessory, Single lever	Single lever with safety switch	
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical F-N-R			
Transmission Ratio	13 / 27			
Available shaft versions	XL	C.- L		XL
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	32	39,9	30,5	32

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## Pike

9.9



## Wahoo

15



## Wahoo

20





# Amberjack E.F.I.

25



## TECHNICAL CHARACTERISTICS

Model	PIKE		WAHOO		AMBERJACK
Power (hp)	9,9		15	20	25 <b>EFI</b>
Power (kW)	7,3		11	14,7	18,4
Max. R.P.M.	5000 / 6000				
Motor type	4 temps SOHC				
Swept volume c.c.	212		362		432
Bore x Stroke (mm)	56 x 43		63 x 58,1		65 x 65,1
N° Cylinders	2 in-line				
Induction	1 carburettor				Electronic Injection
Choke	Manual		Automatic		
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Separate 12			Separate 23	
Lubrication	Forced (oil sump)				
Ignition	C.D.I. Micro-computer				
Ignition timing	Electronic				
Starting	Manual or Electric				
Alternator	Standard 12V/70W (regulator optional) on Manual start version Standard 12V/70W with regulator on Electric start version		Standard 12V/120W (regulator optional) on Manual start version Standard 12V/120W with regulator on Electric start version		Standard 12V/190W (regulator optional) on Manual start version Standard 12V/190W with regulator on Electric start version
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater through propeller				
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version				
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch				
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters		Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version		Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version
Gears	Mechanical F-N-R				
Transmission Ratio	13 / 27				
Available shaft versions	C. - L.				
Standard propeller type	3-bladed with built-in spring drive				
Weight basic version (kg)	39,9		51,7		56

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).  
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

**Aruana** E.F.I.

40



**Dorado** E.F.I.

50



**Dorado** E.F.I.

60



**Murena E.F.I.**

**70**



# TECHNICAL CHARACTERISTICS

Model	ARJANA		DORADO		MURENA
Power (hp)	<b>40 EFI</b>		<b>50 EFI</b>	<b>60 EFI</b>	<b>70 EFI</b>
Power (kW)	29,4		36,8	44,1	51,5
Max. R.P.M.			5000 - 6000		5300 - 6300
Motor type			4 Stroke SOHC		4 Stroke SOHC - 16V
Swept volume c.c.	747		996		
Bore x Stroke (mm)			65 x 75		
N° Cylinders	3 in-line		4 in-line		
Induction			Electronic injection		
Choke			Automatic		
Fuel			Petrol (for specifications see the user manual)		
Fuel tank (L)			Separate 23		
Lubrication			Forced (oil sump)		
Ignition			T.C.I./Computer		
Ignition timing			Electronic		
Starting			Electric		
Alternator	Standard 12V/190W with regulator		Standard 12V/200W with regulator		
Cooling			Water cooled with pump-forced circulation		
Exhaust			Underwater through propeller		
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box, depending on the version		Remote with remote control box		
Type of remote control box provided (for the version with remote control box)			Single remote control box with safety switch		
Trim adjustment	Servo-assisted with Hydraulic shock absorber or Power Trim/Tilt depending on the version		Power Trim/Tilt		
Gears			Mechanical F-N-R		
Transmission Ratio	13 / 26		13 / 24		12 / 28
Available shaft versions			L		L-XL
Standard propeller type			3-bladed with built-in spring drive		
Weight basic version (kg)	99		111		119

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## Spearfish E.F.I.

80xs/100



## Swordfish E.F.I.

115



## Killer Whale E.F.I.

150





## Sei Whale E.F.I.

200



## TECHNICAL CHARACTERISTICS

Model	SPEARFISH		SWORDFISH	KILLER WHALE	SEI WHALE
Power (hp)	80 XS EFI	100 EFI	115 EFI	150 EFI	200 EFI
Power (kW)	58.8	73.6	84.6	110.3	147.1
Max. R.P.M.	5000 / 6000		5300 / 6300	5000 / 6000	
Motor type	4 Stroke SOHC - 16V		4 Stroke DOHC - 16V		4 Stroke DOHC - 16V at variable timing
Swept volume c.c.	1832			2670	2785
Bore x Stroke (mm)	81 x 88.9			94x96.2	96 x 96.2
N° Cylinders	4 in-line				
Induction	Electronic Injection				
Choke	Automatic				
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Not provided				
Lubrication	Forced (oil sump)				
Ignition	T.C.I./Computer				
Ignition timing	Electronic				
Starting	Electric				
Alternator	Standard 12V/420W with regulator				Standard 12V/500W with regulator
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater through propeller				
Steering system	Remote with remote control box				Remote control box with electronic control Drive By Wire
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch			Single binnacle lever with safety switch	Single lever with electronic binnacle Drive by Wire with safety switch
Trim adjustment	Power Trim/Tilt				
Gears	Mechanical F-N-R				Mechanical F-N-R electronic, operating Drive by Wire
Transmission Ratio	13/28			14/28	14/26
Available shaft versions	L - XL				XL
Standard propeller type	3-bladed with built-in spring drive				
Weight basic version (kg)	162	175	216	227	

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

## Beaked Whale E.F.I.

225



## Right Whale E.F.I.

250



# White Whale E.F.I.

300



## TECHNICAL CHARACTERISTICS

Model	BEAKED WHALE	RIGHT WHALE	WHITE WHALE
Power (hp)	225 EFI	250 EFI	300 EFI
Power (kW)	165,5	183,9	220,7
Max. R.P.M.	5000/6000		
Motor type	4 stroke DOHC - 24V with VTC direct acting		
Swept volume c.c.	4169		
Bore x Stroke (mm)	96 x 96		
N° Cylinders	6 a V 60°		
Induction	Electronic Injection		
Choke	Automatic		
Fuel	Petrol (for specifications see the user manual)		
Fuel tank (L)	Not provided		
Lubrication	Forced (oil sump)		
Ignition	T.C.I. / Computer		
Ignition timing	Electronic		
Starting	Electric		
Alternator	Standard 12V / 840W with regulator		
Cooling	Water cooled with pump-forced circulation		
Exhaust	Underwater through propeller		
Steering system	Remote control box with <b>electronic control Drive By Wire</b>		
Type of remote control box provided (for the version with remote control box)	Single lever with electronic binnacle Drive by Wire with safety switch		
Trim adjustment	Power Trim/Tilt		
Gears	Mechanical F-N-R , electronic, operating Drive by Wire		
Transmission Ratio	21/12		
Available shaft versions	XL	XL - UL	
Standard propeller type	3-bladed with built-in spring drive		
Weight basic version (kg)	260		

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

COUNTER ROTATING PAIR

**Sei Whale** E.F.I.

2x200



COUNTER ROTATING PAIR

**Beaked Whale** E.F.I.  
**Right Whale** E.F.I.

2x225/250



COUNTER ROTATING PAIR



## White Whale E.F.I.

2x300



COUNTER ROTATING PAIR

# TECHNICAL CHARACTERISTICS

Modello	COUNTER ROTATING PAIR SEI WHALE	COUNTER ROTATING PAIR BEAKED WHALE	COUNTER ROTATING PAIR RIGHT WHALE	COUNTER ROTATING PAIR WHITE WHALE
Power (hp)	2 x 200 EFI	2 x 225 EFI	2 x 250 EFI	2 x 300 EFI
Power (kW)	2 x 147,1	2 x 165,5	2 x 183,9	2 x 220,7
Max. R.P.M.	5000 / 6000			
Motor type	4-stroke DOHC - 16V at variable timing	4 stroke DOHC - 24V with VTC direct acting		
Swept volume c.c.	2 x 2785	2 x 4169		
Bore x Stroke (mm)	2 x 96 x 96,2	2 x 96 x 96		
N° Cylinders	2 x 4 in linea	2 x 6 a V 60°		
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Not provided			
Lubrication	Forced (oil sump)			
Ignition	T.C.I. / Computer			
Ignition timing	Electronic			
Starting	Electric			
Alternator	Standard 12V/500W with regulator	Standard 2 x 12V/840W with regulator		
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Remote control box with electronic control Drive By Wire			
Type of remote control box provided (for the version with remote control box)	Twin lever with electronic binnacle Drive by Wire with safety switch			
Trim adjustment	Power Trim/Tilt			
Gears	Mechanical F-N-R electronic, operating Drive by Wire			
Transmission Ratio	14/26	21/12		
Available shaft versions	XL			XL - UL
Standard propeller type	3-bladed with built-in spring drive, counter rotating pair			
Weight basic version (kg)	2 x 227	2 x 260		

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

# ACCESSORIES

## AVAILABLE ENGONES CONTROL

### Mechanical controls



### Drive by wire controls



### Digital screen



## Available propellers



GS aluminium series  
for Aruana and Dorado



KS aluminium series  
for Murena, Spearfish and Swordfish



KS Series Inox polished  
for Spearfish and Swordfish



MS Series Inox polished  
for Killer Whale and Sei Whale



TS Series Inox polished  
for Beaked Whale, Right Whale and  
White Whale



MXS Series In polished stainless steel  
CNC precision machined  
for Killer Whale and Sei Whale



TXS Series In polished stainless steel  
CNC precision machined  
for Beaked Whale, Right Whale and  
White Whale



MS4 Series Polished stainless steel 4-blade  
for Killer Whale, Sei Whale, Beaked  
Whale, Right Whale and White Whale



**Engines Plus Ltd**  
 UK Distributor & Eire Sales Agent  
 Tel - + 44 (0) 1452 729707  
 e-mail - [marinesales@enginesplus.co.uk](mailto:marinesales@enginesplus.co.uk)  
[www.enginesplus.co.uk](http://www.enginesplus.co.uk)



[www.selvamarine.com](http://www.selvamarine.com)

